

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 02-018482

(43)Date of publication of application : 22.01.1990

(51)Int.Cl.

C09J 7/02

C09J 7/02

(21)Application number : 63-169893

(71)Applicant : NITTO DENKO CORP

(22)Date of filing : 06.07.1988


(72)Inventor : AIZAWA KAORU
ONE TATSUHIKO

(54) PRODUCTION OF TACKY MEMBER OF FOAMABLE MATERIAL BASE

(57)Abstract:

PURPOSE: To enlarge anchor effects, to firmly retain a pressure-sensitive adhesive layer on an expanded base, to raise air permeability by high voids and to improve bond strength to a material to be bonded by extending a fibrous pressure-sensitive adhesive on the surface of expanded base to form a pressure-sensitive adhesive layer of porous structure.

CONSTITUTION: A fibrous pressure-sensitive adhesive 21 is extended on the surface of a porous expanded base 1 to form a pressure-sensitive adhesive layer 2 of porous structure. The prepared tacky member has air permeability in the extending direction of pressure-sensitive layer, excellent uniform distribution of bonding contributing point, large bond area and reduced unevenness of bond strength to expanded base and materials to be bonded.



LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office